

WEDGE HB 532 2kHz

Spec. #: WHB18A02

High Peak Power Diode Pumped Solid State Laser



FEATURES

- _ Up to 1 mJ
- _ Short pulse duration
- _ Q-Switching up to 2 kHz
- _ All Solid State Design
- _ Air Cooled
- _ Low heat waste

Technical Specifications

Wavelength	532	nm
Pulse energy	Up to 1	mJ
Pulse Width @ 2 kHz	< 1.5	ns
Repetition Rate	Single shot to 2 kHz	
Polarization	Linear 100:1	
Beam Diameter	< 1.5	mm
Beam Divergence	< 6	mrad
Beam Quality	$M^2 < 3.5$	
Electrical Requirements	DC Power Supply 8 V ; 15 V (*)	
Cooling	Air Cooled	
Mechanical Dimensions	26 x 22 x 8	cm ³
Weight	< 10	kg

(*) Optional: 100-230 VAC Power Supply




All information included in this document is subject to change without notice.

Update data sheets can be provided after formal request.

For complete details, please contact your local **Bright Solutions** sales representative or visit our website at www.brightsolutions.it

Bright Solutions Srl
 Via Artigiani, 27
 27010 Cura Carpignano - PV
 Italy
Ph. +39 0382583094
e-mail: sales@brightsolutions.it

Mechanical drawing



All dimensions are in millimeters

Options Available:

- Beam Expanding and Collimating optics (external)
- Circular Polarization
- Water Cooling

Applications:

- Machining of glass and hard materials
- Non-linear spectroscopy
- Visible to IR OPO pumping
- Specialty Marking



All information included in this document is subject to change without notice.

Update data sheets can be provided after formal request.

For complete details, please contact your local **Bright Solutions** sales representative or visit our website at www.brightsolutions.it

Bright Solutions Srl

Via Artigiani, 27
27010 Cura Carpignano - PV
Italy

Ph. +39 0382583094

e-mail: sales@brightsolutions.it