

(6+1)×1 Multi-Mode Pump Combiner (MPC)

Description



This (6+1)×1 multi-mode fiber combiner is designed for high power EDFA application. It combines six pump lasers and one signal channel into one double cladding output fiber. Fiber type can be customized.

Key Features


- High Signal Transfer Efficiency
- High Pump Efficiency
- Wavelength Insensitive
- Custom Configurations Available

Mechanical Dimension


C1: 50x5x5



C2: Ø4x60



C4: 70x12x8



Unit: mm

Specifications

Parameters/Test conditions		Min	Typ.	Max	Unit	Note
1	Signal Operating Wavelength	1500	1550	1600	nm	
2	Pump Operating Wavelength	800		1000	nm	
3	Pump Fiber	Core Diameter		105	μm	Refer to fiber codes
4		Cladding Diameter		125	μm	
5		Numerical Aperture	0.15		-	
6	Signal Fiber	SMF-28e (XB) or 1550GDF or DCF-UN-8/125-14				Refer to fiber codes
		Pump Efficiency (%)		Signal Insertion Loss (dB)		Power Handling (W, each port)
7	Output Fiber	1550GDF	>90 (Typ. 93)		<0.7 (Typ. 0.5)	25
		DCF-UN-8/125-14	>90 (Typ. 93)		<0.7 (Typ. 0.5)	25
8	M ²			1.3	-	
9	Optical Isolation	20			dB	
10	Fiber Length	0.8			m	Each port
11	Operating Environment Temperature	-5		+70	°C	
12	Operating Humidity	5		95	%RH	Not recommend in high humidity for long time.
13	Storage Temperature	-40		+85	°C	
14	Package	C1, C2, C4			-	Handling power is different with PKG

Ordering Information

MPC-(6+1)×1-F(B)-Pump wavelength/Pump power-Signal wavelength-Pump fiber/Signal fiber-Output fiber-Package-Fiber length

Note :

F: Forward pump; B: Backward pump.

Pump/Signal/Output fiber: refer to fiber codes.

Package: C1, C2, C4

C1: 5W/port; C2: 5W/port; C4: 25W/port